



AGM Battery (Absorbent Glass Mat)

MODEL	Voltage / V	Capacity / Ah		RC/min	CCA(A)	Dimension(mm)			Dimension(Inch)			Weight /±2%	Terminal
		20HR	5HR			Length±2	Width±2	Height±3	Length ±0.08	Width ±0.08	Height ±0.12		
AGM- L0	12	40	32	60	460	175	174	190	6.89	6.85	7.48	12.5	STD
AGM- L1	12	50	40	80	570	207	174	190	8.15	6.85	7.48	15.0	STD
AGM- L2	12	60	48	100	660	241	174	190	9.50	6.85	7.48	18.2	STD
AGM- L3	12	70	56	120	720	277	174	190	10.91	6.85	7.48	21.0	STD
AGM- L4	12	80	64	140	800	315	174	190	12.41	6.85	7.48	24.0	STD
AGM- L5	12	92	73	160	850	353	174	190	13.91	6.85	7.48	26.8	STD
AGM- L6	12	105	84	190	950	393	174	190	15.48	6.85	7.48	29.7	STD
AGM- G31	12	80	64	140	800	325	172	220	12.81	6.78	8.67	25.8	TM
AGM- B20	12	36	29	53	300	195	128	220	7.68	5.04	8.67	11.2	SM/STD



START - STOP BATTERY

Model	Voltage (V)	Capacity(Ah)	Dimension(mm)				CCA (±5%)	Layout	Terminal	Group
		20HR	L	W	H	TH				
EFB - K42/M42	12	36	195	128	198	219	460	0/1	SM	B19/20
EFB - N55	12	45	237	127	200	222	550	0/1	SM/STD	B24
EFB - Q85	12	65	231	172	201	223	740	0/1	STD	D23
EFB - S95/S85	12	70	259	174	202	225	830	0/1	STD	D26
EFB - T115/T105	12	80	300	173	201	222	950	0/1	STD	D31
EFB - E41	12	100	406	171	205	227	1050	0/1	STD	E41
EFB - 40LB1	12	40	207	175	175	175	550	0/1	STD	LB1
EFB - 44L1	12	44	207	175	190	190	560	0/1	STD	L1
EFB - 50LB2	12	50	239	173	174	174	760	0/1	STD	LB2
EFB - 62L2	12	62	239	173	188	188	760	0/1	STD	L2
EFB - 65LB3	12	65	275	174	174	174	850	0/1	STD	LB3
EFB - 70L3	12	70	271	174	185	185	850	0/1	STD	L3
EFB - 80L4	12	80	315	175	190	190	980	0/1	STD	L4
EFB - 75T7	12	75	315	175	175	175	1000	0/1	STD	LB4
EFB - 90LB5	12	90	353	174	175	175	1020	0/1	STD	LB5
EFB - 100L5	12	100	349	172	187	187	1020	0/1	STD	L5